



## Specifications

### Capacity

|           |  |
|-----------|--|
| Fuel tank | 86.3 litres (18.9 gallons) (22.7 US gallons) |
|-----------|--|

### General Specification

| Item                        | Specification  |
|-----------------------------|--|
| System type                 | Mechanical - returnless  |
| Fuel delivery module        | Located in the fuel tank   |
| Fuel pump:                  |  |
| Type/location               | Electric - submersible - located in the fuel tank  |
| Operating pressure          | 450 kPa (4.5 bar) (65.25 lb/in <sup>2</sup> )  |
| Maximum output @ 12.3 volts | 122 litres/hour (26.8 gallons/hour) (32.2 US gallons/hour)   |
| Fuel pressure regulator:    |  |
| Type/location               | In-line, within fuel tank  |
| Operating pressure          | 450 kPa (4.5 bar) (65.25 lbf/in <sup>2</sup> )   |
| Fuel filter                 | Located in the fuel delivery module - fitted with a renewable element  |
| Fuel tank sender units      | Two - Front and rear - Front unit is located remotely within the fuel tank, rear is mounted on the body of the fuel pump |

### Torque Specifications

| Description                  | Nm  | lb-ft |
|------------------------------|-----|-------|
| Fuel tank bracket bolts      | 10  | 7     |
| Fuel tank bolts              | 45  | 33    |
| Fuel tank heat shield, bolts | 5   | 4     |
| Fuel tank heat shield, nuts  | 3   | 2     |
| Fuel pump module clamp screw | 4   | 3     |
| Fuel tank filler pipe bolt   | 10  | 7     |
| Road wheel nuts              | 140 | 103   |